

ANCHOR SHEET ATTACHMENT DEVICES**INTRODUCTION TO THE INVENTION**

Sub C1) This invention concerns improvements to attach a flexible but relatively rigid anchor
5 sheet for use under carpets or other decorative coverings as described in current inventor's
U.S. applications 08/850,726 filed May 2, 1997, 09/008,565 filed January 16, 1998 and
09/008,584 filed January 16, 1998. This application incorporates by reference the teachings
of these earlier applications except where those teachings may have been modified by new
developments as set out herein. The current inventor has invented an anchor sheet which,
10 when installed, acts to tie decorative covering together as a functional unit and to add mass
and stability to such unit, particularly in the case of a unit having a flexible decorative
covering such as a carpet. The anchor sheet may be substantially covered over one side with
hooks for anchoring a decorative covering to it by engagement of complementary loops on
the under side of the decorative covering. The anchor sheet itself may be attached to the
15 underlying substrate, such as a floor or wall, or it may be loose laid on a floor where the
anchor sheet can have sufficient mass so as to prevent movement of the anchor sheet. The
present invention provides attachment devices so as to minimize attachment of the anchor
sheet to the underlying substrate, and to allow for the possibility of spacing between anchor
sheet units in order to accommodate atmospheric changes. It is possible to supply the anchor
20 sheet in modular units of various geometric shapes and sizes with corresponding
complementary corner pieces.

BACKGROUND OF THE INVENTION

The earlier cases by the same inventor Pacione disclose an anchor sheet which can be
25 supplied as a small or large module, with or without a pre-attached decorative covering.
These earlier cases also disclose the anchor sheet as a modular unit which can form a
contiguous mass of anchor sheet. Such a contiguous mass can be formed by attaching the
anchor sheets together by some form of overlap or by abutting the anchor sheets to each other
and using an overlap of decorative covering or tape. Such mass can be free floating or
30 attached to the floor.

SUMMARY OF THE INVENTION

The current invention relates to attachment devices for such modular anchor sheets which when abutting or overlapped can be held to the underlying floor by the use of the attachment devices or glued together by use of the attachment devices so as to form totally or partially free floating units. In particular, if the attachment devices are attached to the underlying substrate by means of the structure shown in this application, the anchor sheets can be made more relatively free floating, which can provide for expansion and contraction between the modular sheets.

There are advantages to having the anchor sheet attached at only a few discrete attachment points, or even in some cases not attached at all so as to be easily removeable. If the anchor sheet covering is formed from modular units and is attached in such a way that there is some relative movement between the modules, this will allow for a more stable anchor sheet product which can expand and contract to accommodate atmospheric changes such as temperature and humidity. It is envisaged that the anchor sheet can be made of polyethylene or polypropylene, but even these materials change in size as much as one-quarter inch over the size of a normal room because of temperature changes. Therefore, there are advantages to allowing some form of spacing or floating between the modular units. In addition, there are advantages to providing for a system whereby the anchor sheets form a contiguous mass without a large number of attachment locations to the underlying substrate and without having to drill through the anchor sheets themselves.

Frequently, it is advisable to form a two-layer anchor sheet as shown, for instance in Figure 31 in Patent Application No. 09/008,565. The top and bottom layers are offset from each other so as to form an overlap or underlay on each module matched with the corresponding overlap or underlay on a corresponding module. Two layers can be attached by hook and loop or glued, co-extruded together, or injection moulded to form a modular piece. Typically, such modular piece would be in the form of a square tile. Typically, areas where the tiles abut, particularly the corners, could be areas of weakness where the anchor sheet might shatter or break, or where areas of discontinuity on the surface of the anchor sheet may become apparent.

In order to minimize attachment of these modular forms of anchor sheet to the underlying substrate and also to provide for the possibility of floating between such anchor sheets, the applicant has invented a new attachment structure which includes a modification to the anchor sheet itself generally at the corners and a corresponding complementary corner-
5 piece in a matching geometric relationship which presses and holds the four corners together to the substrate while at the same time allowing for the anchor sheets to ride underneath the cornerpiece when required in order to provide for expansion and contraction.

Thus, the invention in one aspect consists of an anchor sheet having edges and
10 comprising a generally polygonal anchor sheet having a cut of a pre-determined first geometric shape reducing the thickness of the anchor sheet in a first area surrounding the apex of the angles of the edges of the sheet, the sheet having a second cutaway portion of a smaller second area within the first area of a pre-defined second geometric shape, so that when the anchor sheet is laid side by side along its straight edges with a corresponding
15 anchor sheet, the respective first area and second area line up to form a first reduced thickness area at the corner surrounding the point where the apexes of the sheets would have met and a second cut-away area within the first area so that the anchor sheet is cut away at the point where the apexes of abutting anchor sheets would otherwise meet.

20 Matching the geometric areas formed by the first reduced thickness area and second cutaway portions of the polygonal anchor sheets are complementary matching cornerpieces. The complementary matching cornerpieces are in their area of maximum thickness the same as the thickness of a complementary anchor sheet, and are of an overlapping geometric shape matching the first reduced thickness portion and having an underlay matching the second cut
25 away geometric shape defined by the abutting anchor sheets.

The invention can also be adapted to anchor sheets which are overlapped as previously described in the Pacione applications referred to above. In this aspect the invention consists of an anchor sheet for anchoring a decorative covering to a floor in which a
30 generally polygonal sheet having at least one edge which has a lower portion which has been cut away to create an overhanging area of anchor sheet along that edge and a first lower portion edge under the overhang and at least a second edge of the anchor sheet has an upper portion cut away to create an underlaying area of a second lower portion edge along that

second edge so that the overhanging area of one anchor sheet can overlap the underlaying area of an abutting second anchor sheet, the improvement which comprises a first area of reduced thickness surrounding the apex of the angles formed by the edges of the first and second lower portions and a second smaller area within the first area cut away around the point where the apexes of lower portions of abutting anchor sheets would meet.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows an anchor sheet in a simple form with an underpad according to this invention.

10 Figure 2 shows an anchor sheet in plan view having overlapping edges in addition to the cutaway portions for the cornerpieces.

Figure 3 shows the cornerpiece to be used with certain geometric shapes of anchor sheets.

Figure 4 shows the anchor sheet and corner piece (in partial section).

15 Figure 5 shows a corner piece in section with attached cushion and countersunk attachment points.

Figure 6 is a section view of an anchor sheet along the lines 6-6 in Fig. 2 (on the same page as Figure 5).

Figure 7 is a plan view of a corner piece (on the same page as Figure 5).

DESCRIPTION OF PREFERRED EMBODIMENTS

As shown in Figure 1, an anchor sheet 1 is provided, which in this case is in the shape of a square, one of the preferred shapes. It is also possible to have the anchor sheet 1 provided in any shape that can be conveniently abutted with another similar piece to create a floor pattern such as, for instance, a rectangle, a hexagon or an octagon. Generally the preferred shape will be an equilateral polygon but a rectangle may also work in some cases. The anchor sheet 1 contains a top surface layer 3 having hooks. In this embodiment anchor sheet 1 also contains the cushion 5 to provide resilience to the anchor sheet and to a decorative covering, such as for example, a carpet overlaid on top of the anchor sheet. However, cushioning is not necessary for the functioning of anchor sheet 1, but such cushioning can have advantages depending on the overlayment to be used and the intended

use of the anchor sheet. In alternative embodiments, cushion 5 may also be replaced with a structure that will provide roughly equivalent resiliency to a cushion 5.

In practice, the hooks of the top surface layer 3 will be attached to the loops of an
5 overlying carpet (not shown) when an entire anchor sheet subfloor has been installed. The
anchor sheet has a thickness A. The appropriate thickness A will depend on the intended use
of the anchor sheet, and may vary with the type of overlayment to be used. The thickness A
will not be substantially less than 0.020 inches and generally will not be less than 0.062
inches. The preferred thickness A is around 0.125 inches, but the thickness A may be as
10 much as 0.75 inches, for example in situations where a thick floor is to be replaced, or where
a thick anchor sheet needs to be used to create a level surface with an adjacent surface.
Cutaway from that thickness is an area 7 which will be shaped into some geometric shape, in
this case a portion of a circle, so that when combined with similar abutting anchor sheets
aligned along sides 9 and 11, a $\frac{3}{4}$ circular cut out area will be formed. A fourth anchor sheet
15 diagonally opposite anchor sheet 1 will form a complete circle having a circular cut out area
and a "hole" 14 as described below. Typically, the cut-out area will be such that the width of
the anchor sheet at 13 will be approximately half of the total thickness A of the anchor sheet.
However, the width of the anchor sheet at 13 may be other than approximately half the total
thickness A and still incorporate the teachings of this patent. In addition, there is a second
20 area 14 which has been cut away from the corner (the apex of the angle formed by the two
sides of the square). This second area 14 also has a geometric shape, in this example a $\frac{1}{4}$ of a
circle, so that when combined with other anchor sheets, the anchor sheet edges are lined up so
that their corners meet at the imaginary intersection of the four corners, and a second smaller
circle will be formed in the completed anchor sheet structure.

25

Thus, a circular cut away area 14 within a second larger circular cut out area 7 is
created when four similar anchor sheets abut each other as shown in Figure 2. A
complementary corner piece can then be added which will match the shape and thickness of
the reduced thickness portion and the shape and thickness of the cutaway area as shown in
30 Figures 3 and 4. This corner piece can be attached to area 7 by glue or other permanent
attachment, or by detachable attachment such as pressure sensitive adhesive or a hook and
loop. Fastening devices such as hook and loop or a screw or nail can be used to attach the

corner pieces to a floor thereby holding the anchor sheet to the floor at only a few discrete points by use of the corner pieces, with or without direct attachment to the anchor sheets.

Only a minimal number of corner pieces may need attachment to the floor to stabilize the unit. The corner pieces generally need to be attached to the anchor sheet or to the floor. In some cases, the corner pieces are not attached to the floor but only to the anchor sheets themselves so as to allow the complete unit to float freely over the floor. If the corner pieces are only attached to the floor, the anchor sheets can "ride" under them. In some installations, some of the corner pieces will be attached to the floor while other corner pieces are only attached to the anchor sheets.

Alternatively, if the corner pieces are attached to the anchor sheets at area 7 by glue or some other means of attachment, then the whole unit can free float by not attaching the corner pieces to the floor.

The arrangement of anchor sheet modules and corner pieces where there are overlapping anchor sheets can be seen in Figure 2. In Figure 2, a plurality of anchor sheets 111 are shown. In this example they are squares. Unlike the embodiment in Figure 1 however, these anchor sheets 111 do not abut each other in one plane only. Rather, the anchor sheets 111 in this embodiment have an underlay area 15 in which there is a lower portion edge 16. Underlay area 15 is indicated in Figure 2 by a grid marking, but underlay area 15 is part of anchor sheet 111. Underlay area 15 lies under the overlap area 19 on an adjacent sheet. The overlap area 19 in this example extends on two sides of each sheet, whereas the underlay area 15 extends on the other two sides. The overlap area 19 overlaps the underlay area 15 of each sheet, for instance along the area 20 shown in Figure 2 (the area between the top abutment edge at the dotted line). An area of reduced thickness 21 is formed surrounding where the apex of the underlay edges 15 would have been of the square. In this case, the cutout is centred over the area of abutment for instance at 23 of the lower portion edges of the anchor sheet. It is not centred over the corner line of abutment 25 created by the overlap edges extending over the area of overlap 19. In addition to the reduced thickness area 21 (similar to area 7 in Figure 1) there is a completely cutaway portion 23.

Figure 3 shows a corner piece 31 which consists of a lower portion 33 which matches in geometric shape the cutaway portion 35 shown in Figure 3, a shape that will be formed by all of the abutting pieces 37 of lower edge portions of anchor sheet. (This lower portion 33 will therefore normally be shaped to correspond to the shape of the cut away portion 23 from Figure 2) In this case, it is a simple circle. This will be the preferred shape, although, of course polygons or other shapes are also possible and the upper portion of the corner piece 39 need not be the same shape as the cut away portion 35.

The upper portion of the corner piece 39 will be shaped to correspond to the cutaway portion 41. Again, this is a circle but could be another shape, particularly an equilateral polygon. In Figure 3 the corner piece could be attached to the anchor sheet in the cutaway portion area 41 and thus form an attachment between four contiguous anchor sheets modules. Typically, if the corner pieces are attached to the floor but not to the anchor sheets, the radius of lower portion 33 will be less than the radius of cut-away portion 35, and the radius of upper portion of corner piece 39 will be less than the radius of cutaway portion 41 to allow for atmospheric expansion of the anchor sheets.

In cases where the corner pieces are only going to be attached to the anchor sheets (allowing the anchor sheets and corner piece subfloor to free-float over the floor), it is not necessary to have cut-away portion 35 in the anchor sheet and corresponding lower portion 33 in the corner piece. In this case, the lower surface of upper portion of the corner piece 39 will be attached to cutaway portion 41.

Figure 4 shows illustrates the use of corner pieces 31 of Figure 3 with the anchor sheets 111 of Figure 2. Corner pieces 31 are shown in partial section view. Specific corner piece 113 is shown placed within circle 115 created by the corners of the four adjacent anchor sheets 111.

The corner pieces 31 could be attached to the underlying floor by use of a screw 42 as shown in Figure 7, or the anchor sheet could remain free-floating if there is sufficient mass to provide for stability, particularly when an overlying decorative covering, such as a carpet, is attached to the anchor sheet. Space 119 may be maintained in the screw hole 121 by having

the radius of screw hole 121 be larger than the radius of screw 42, allowing for movement of the corner pieces 31.

As shown in Figure 5, it is also possible to have the screw countersunk. In this case if the anchor sheet has a cushion 45, a rigid layer 43 is provided attached to the cushion 45. A plug 47 is removed from the rigid layer 43 and cushion 45. After the screw has been attached to the subfloor, the plug 47 is reinserted to create a smooth upper surface of cushion and anchor sheet, or the plug can simply be filled with cushion or any other suitable material.

Figure 6 is a section taken along the line 6-6 in Figure 2. It shows corner pieces 51 which overlap areas of reduced thickness 53 on anchor sheets 55. The anchor sheet 55 can be free to ride between two corner pieces 51, especially if there has been a tolerance or space built in to the spacing between anchor sheets 55 and corner pieces 51 as described above. In this case, corner pieces 51 would normally be attached to the underlying substrate with a screw (not shown). It is also possible to attach the corner pieces partially or wholly to the anchor sheets 55 through attachment to areas of reduced thickness 53, in which case in some instances it may not be necessary to attach any corner pieces 51 to the substrate, instead letting anchor sheets 55 and corner pieces 51 float on the substrate.

Attachment of corner pieces at the corner reduces the number of attachment points required, because each corner piece overlaps four sheets at one corner. Because the corners of anchor sheets are an area of weakness (as previously stated) there is less likely to be discontinuities or breakage with this attachment system. In addition, because fewer attachment points are required there is less degradation to the integrity of the anchor sheet because there are fewer holes in the anchor sheet. Finally, because the corner pieces hold the anchor sheets down without necessarily attaching them to the underlying floor it is possible to allow for movement of the anchor sheets in relation to the corner pieces, including the handling of atmospheric expansion.

While corner pieces have been described, it is possible to use the invention by providing a reduced thickness area along any edge of a modular anchor sheet and having a cut away area within the reduced thickness area to provide a structure for use of the attachment devices described at that point. A reduced thickness area surrounding a cut away

area may also be located anywhere in the interior of an anchor sheet for use of the attachment devices at that interior point.

In embodiments where the anchor sheet modules are attached to the floor only
5 through the corner pieces, the anchor sheet modules can easily be removed and replaced if they are defective or require repair.

It is expected that the modules would likely be square, and preferably in the range of
four feet by four feet to two feet by two feet, although modules outside of this range are also
10 functional and fall within the scope of this invention.

The anchor sheet modules could be made of an extruded or molded material in which
the two pieces are thermally bonded so as to form an overlap and underlay. The sheets could
be cut by a gauge or jig. The anchor sheet modules could be die cut. A layer of hooks could
15 be thermally bonded to the surface of the top sheet. Alternatively, the complete module
(potentially including hooks, and the two "layers" of the module) could be injection-molded
using a one- or two- step or multi-step process mold, using materials such as polypropylene
or polyethylene.

20 The overlap and underlay areas of the modules may be provided with means for
detachable or permanent attachment, or the underlay areas may simply lie underneath and
support the overlap areas without any form of attachment. Alternatively, the modules may
also be made with corresponding registering bumps and indentations (not shown) in the
overlap and underlay portions of the modules to assist in retaining the modules together and
25 in alignment during installation.

In all cases where hook and loop systems or hooks are provided for, the hooks may be
temporarily covered by a hard slip covering as discussed in U.S. Application No. 08/850,726
or a soft covering as disclosed in U.S. Patent 4,822,658 to temporarily prevent premature
30 engagement of the hooks to loops.

It is noted that those skilled in the art will appreciate that various modifications of detail may be made from the embodiments described herein which would come within the spirit and scope of the invention as described in the following claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
221